## OFFICE OF THE EXECUTIVE ENGINEER SOUTH EASTERN DIVISION NO.11 DDA VIKAS SADAN NEW DELHI

F.6 (2)/EE/SED-11/DDA/2009-10 11664

Dated: 16/12/05

## PRESS TENDER NOTICE OF EE/SED-11/DDA/2009-10

Sealed item/percentage rate tender are invited for the following works on behalf of the DDA from the approved and eligible contractors of appropriate class of DDA, (County MIDS) PACE County (Maintage up to 3.00 PM on the date of opening (mentioned below), which shall be opened on the same day at 3.30 PM at 1st Floor, Press Building, Vikas Sadan, INA, New Delhi-23 by the Executive Engineer/SED-11/DDA in the presence of the contractors or their authorized representatives. Tender documents can be had on any working day from the date of circulation between 11.00AM to 3.00PM on payment of the cost of tender + D Vat (non-refuncable) mentioned against each work, on production of valid enlistment certificate, certificate of registration with Works Contract Cell of Sales Tax Deptt. of the GNCTD and the clearance certificate in Form XI form CAU/SZ/DDA/ Shahpur Jat, New Delhi and Centralized Fender Office at Vikas Sadan, INA, New Delhi-23. The sale of tender will be stopped four days before the date of opening (including the date of

The contractors can submit their tender in sealed envelope only up to seven days before the date of opening between 10.00AM to 5.00 PM except the date of opening when it will be up to 3.00 PM. The tender can also be sent by the contactors through Registered Post,

which should reach the Office of the EE/SED-11DDA at least one day before the last date of the receipt of tenders.

The manner of submission of tender, opening of the same and entry of contactors/their representatives to the place of opening

shall be as provided in clause-3(a) (b) and (c) of the PWD-6 forming part of tender documents.

The Earnest Money shall accompany the tender in the form of Call at Deposit Receipt or Demand Draft of a scheduled Bank guaranteed by the Reserve Bank of India in favour of Sr. AO/CAU/SZ/DDA. The tender of the contractor who does not enclose the carnest money in prescribed manner shall be summarily rejected.

Name of Work & Sub-head

Estimated Cost Earnest Money

Cost of Tender Time Allowed

## NIT, NO. 81/EE/SED\_11/DDA/09\_10

M/O various colonies under South Zone, SH: Repair and maintenance of Staff Flats at A. G. V. Complex

Copy to:-

F.O to CE (SZ), DDA. He is further requested to make arrangements for publication in the leading new paper and through DDA

Website. A copy of Budget slip issued by Sr. AO (CAU) SZ, DDA is attached.

Esst. Cost R 2,85 466-E.Money B 17,709-T. Allowed - 1(000) yeur

## SCHEDULE OF QUANTITIES

Name of Work: M/o various colonies under South ZonE

SH: Repair and Maintenance of Staff Flats at A.G.V.C.

| CMO | Description of Home  | Offi   | 41.00  | Date / Con | M. more and the second of the second |
|-----|--|--|--|------------|--------------------------------------|
| 2   | de 20 mm   | a de la companya de l |  | ratelasi   | Amountains)                          |
|     |  | (35.00   | Sqm  |            |                                      |
|     | 6mm cement plaster of mix 1:3 (1 cement: 3 fine sand)  | 51.00  | Sqm  |            |                                      |
|     | Providing and fixing certain rods of 1.25mm thick chromium plated brass plate with two chromium plated brass brackets fixed with C.P.brass screws and wooden plugs etc wherever necessary complete                     |  |  |            |                                      |
|     | a) 20mm dia  | 26.00  | THE STATE OF THE S |            |                                      |
|     | Renewing glass panes, with putty and nails wherever necessary:  a) Float glass panes of thickness 4mm  | M 0.00   | Sqm  |            |                                      |
|     | Demolishing cement concrete manually by mechanical means including disposal of material within 50 metres lead as per direction of Engineer-In-Charge a) 1:3:6 or richer mix  | 00'h   | Cum  |            |                                      |
|     | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering. All work upto plinth level: 1:2:4 (1 cement: 2coarse sand: 4 graded stone agg. 20mm nominal size). | 6.00   | Cum  |            |                                      |
|     |  |  | A CONTRACTOR OF THE PERSON OF  | •          |                                      |

|  |  |  |                                   | T  | Î   | T  |   |   |  |
|--|--|--|-----------------------------------|--|---|--|---|---|--|
| andle level), plete wherever and lid. Io Nos ed quality 810 gms: 42.Nos opering 1566: 00 repairs to 29.55.00 repairs to 181 C 10 as shade with 42.Nos er and | ಪ  |  |                                   | 3  | ਰ   | 9  | σ   |   | 7  |
| 8 8 6  | Providing and fixing C.P.brass angle valve for basin mixer and geyser points of approved quality conforming to IS: 8931 a) 15mm nominal bore | Providing and fixing aluminium hanging floor door stopper ISI marked anodized (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with necessary screws etc complete:  a) Twin rubber stopper | b) I wo or more coats on new work | Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade:  a) One or more coats on old work | Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc complete | Providing and fixing C.P.brass shower rose with 15 or 20 mm inlet a) 100mm diamemter | Providing and fixing C.P.brass nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms:  a) 15mm nominal bore | conforming to IS: 7231, with all fittings and fixtures complete including cutting and making good the walls and floors wherever required:  a) W.C.Pan with ISI marked white solid plastic seat and lid. | Providing and fixing white vitreous china pedestal type water close (European type W.C.Pan) with sat and lid, 10mtrs low level white |
| each Sqm Sqm   | 42Nos  |  | 18600                             | 2955.00  | 1586.00   | 42Nos  | 412 Nos   | IO NOS  |  |
|  | each   | each   | Sqm                               | Sqm  | Sqm   | each   | each  | each  |  |
|  |  |  |                                   |  |   |  |   |   |  |

|                | - Company of the Comp |        |   |   |  |                | 9 9 9   |  |
|----------------|--|--------|---|---|--|----------------|---|--|
|                | 120  | 9      | 00  | 7   | 6  | (S.S.)         | 17  | -14.   |
|                | Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead:  a) For thickness of tiles 10mm to 25mm.  |        | Providing and fixing C.P.brass stop cock (concealed) of standard design and of approved make conforming  a) 15mm nominal bore | Structural steel work riveted, bolted or welded in built up sections, trussed and framed work, including cutting, hoisting fixing in position and applying a priming coat o approved steel primer all complete. | Providing and placing on terrace (at all floor levels Polyethylene coverage tank ISI: 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. | -0-0-          | PIF for law mated flat pressed 3 Layer (Medium density) particle board or graded frond particle board 15: 7087 water with one size decorative and office size bad ancing law nation and, type is ere terror grade 15: 12825 number in suches with seven and fittings where ever sepised, edges to be pointed with polywrethane Primer (Fittings to be paid separately) belywrethane Primer (Fittings to be paid separately) | OFF C.P. Brass close hale basin mixer Pillar tap of approved Quality and make, weighing not less than 1970/4 |
|                | 147.00   | 100.00 | 6 Nos   | 80,00   | 5,000.00   | 00<br>00<br>00 | 63.40   | TU Nois  |
| ás             | Sqm  | Ŝ      | E act   | 6   | Permit   | - F            | Soul  | EACH   |
| and the second |  |        |   | 9 4 5 7   |  |                |   |  |

1 00

| Providing wood work in frames of false ceilling partitions etc rawn and put up in position:  a) Klin seasoned and chemically treated Hollock wood  Dismantling -doors, windows and clerestory windows(steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead:  complete and stacking panelled or panelled and glazed shutters for doors, windows and clerestory windows and class teak wood, 35mm thick shutters.  a) Providing and fixing panelling for panelling and glazing in panelled or panelled and glazed shutters 25mm to 40mm thick:  a) Ply wood 5 ply, 9mm thick decorrative plywood both side decorrative veneer (Type-I) conforming to IS 1328 BWR type  Providing and fixing fly proof galvanized M.S. wire gauze to windows and clerestory windows using 4mm thick float glass panes including black enameled ISI marked M.S. butt hinges with necessary screws:  a) Second class teak wood beading 62x19mm  Providing and fixing glazed shutters for doors, windows and clerestory windows using 4mm thick float glass panes including black enameled ISI marked M.S. butt hinges with necessary screws:  a) Second class teak wood, 35mm thick | N  | 2,3   | 24  | 25   | 2/6   | 27  |
|--|--|---|---|--|---|---|
|  | Providing wood work in frames of false ceiling partitions etc rawn and put up in position:  a) Kiln seasoned and chemically treated Hollock wood | Dismantling doors, windows and clerestory windows(steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead:  (a) Of area 3.00 SQUID AND below | Providing and fixing paneled or paneled and glazed shutters for doors, windows and clerestory windows including ISI marked black enameled M.S. butt hinges with necessary screws excluding paneling which will be paid for separately:  a) Second class teak wood, 35mm thick shutters.   | Providing and fixing paneling or paneling and glazing in paneled or paneled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured) paneling for paneled or paneled and glazed shutters 25mm to 40mm thick:  a) Ply wood 5 ply, 9mm thick decorative plywood both side decorative veneer (Type-I) conforming to IS 1328 BWR type  | Providing and fixing fly proof galvanized M.S.wire gauze to windows and clerestory windows using galvanized M.S.wire gauge with average width of aperture 1.4mm in both directions with wire of dia 0.63mm:  a) with 2 <sup>nd</sup> class teak wood beading <b>6</b> 2x19mm  | Providing and fixing glazed shutters for doors, windows and clerestory windows using 4mm thick float glass panes including black enameled ISI marked M.S. butt hinges with necessary screws:  a) Second class teak wood, 35mm thick   |
| Sqm Sqm Sqm Each Cm  | 0.30   | 9 Nos   | 45.00   | 15.00  | 29.00   | 17.00   |
|  | Ç  | Each  | Sqm   | Sq   | Sqm   | Sq  |
|  | ,  | #/ '3   |   |  |   |   |
|  | 7  | and put up in position:  a) Kiln seasoned and chemically treated Hollock wood  0.30   | Providing wood work in frames of false ceiling partitions etc rawn and put up in position:  a) Kiln seasoned and chemically treated Hollock wood  Dismantling doors, windows and clerestory windows(steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead:  ca) ♀ area 3.00 ♀ SQUAL area below | Providing wood work in frames of false ceiling partitions etc rawn and put up in position:  a) Kiln seasoned and chemically treated Hollock wood  Dismantling doors, windows and clerestory windows(steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead:  (a) Of area 3.00 Soud and below  Providing and fixing paneled or paneled and glazed shutters for doors, windows and clerestory windows including ISI marked black enameled M.S. butt hinges with necessary screws excluding paneling which will be paid for separately:  a) Second class teak wood, 35mm thick shutters.  45.00 | and put up in position:  a) Kiln seasoned and chemically treated Hollock wood  a) Kiln seasoned and chemically treated Hollock wood  a) Kiln seasoned and chemically treated Hollock wood  Dismantling doors, windows and clerestory windows(steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead:  complete and stacking within 50 metres lead: complete and fixing paneled or paneled and glazed shutters for doors, windows and clerestory windows including ISI marked black enameled M.S. butt hinges with necessary screws excluding paneling which will be paid for separately: a) Second class teak wood, 35mm thick shutters.  Providing and fixing paneling or paneling and glazing in paneled or paneled and glazed shutters for doors, windows and clerestory windows or rebates to be measured) paneling for paneled or paneled and glazed shutters 25mm to 40mm thick:  a) Ply wood 5 ply, 9mm thick decorative plywood both side decorative veneer (Type-I) conforming to IS 1328 BWR type | a) Kiln seasoned and chemically treated Hollock wood  a) Kiln seasoned and chemically treated Hollock wood  Dismantling doors, windows and clerestory windows(steel or wood) shutter including chowkhats, architrave, holdfasts etc.  complete and stacking within 50 metres lead:  ca) Providing and fixing paneled or paneled and glazed shutters for doors, windows and clerestory windows including ISI marked black enameled M.S. butt hinges with necessary screws excluding paneling which will be paid for separately:  a) Second class teak wood, 35mm thick shutters.  Providing and fixing paneling or paneling and glazing in paneled or paneled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured) paneling for paneled or paneled and glazed shutters 25mm to 40mm thick:  a) Ply wood 5 ply, 9mm thick decorative plywood both side decorative veneer (Type-I) conforming to IS 1328 BWR type with average width of aperture 1.4mm in both directions with wire of dia 0.63mm:  a) with 2 <sup>nd</sup> class teak wood beading 62x19mm  29.00 |

NI

|                          | 38  | 3,5   | 3,4  | ω<br>w   | ω<br>22   | ω  | ű,  | 29   | 28   |
|--------------------------|---|---|--|--|---|--|---|--|--|
| b) 20mm dia nominal bore | Providing and fixing G.I.pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc:  a) Internal work-exposed on wall  15mm dia nominal bore. | Providing and fixing 50mm bright finished brass cup board or wardrobe knob with necessary screws (best make of approved quality). | Providing and fixing bright finished brass handles with screws etc complete:  a) 125mm | Providing and fixing bright finished brass night latch including necessary screws etc complete (best make of approved quality) | Providing and fixing bright finished bras 100mm mortise latch and lock with 6 levers and paid or lever handles with necessary screws etc complete (best make of approved quality) | Providing and fixing special quality bright finished brass cupboard or ward robe locks with four levers including necessary screws etc complete (best make of approved quality:  a) 65mm | Providing and fixing bright finished brass tower bolts (barrel type) with necessary screws et complete:  a) 200x100mm | Providing and fixing teak wood lapping of size 25x3mm in pelmet. | Providing and fixing 600x450mm beveled edge mirror of superior glass (of approved quality) complete with 6mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete. |
| 3                        | 30.00   | 28 Nos  | 48 Nos   | 15 No  | 50 Nos  | 28 Nos   | 18 Nos  | 111.00   | 10 Nos   |
|                          | *   | Each  | Each   | Each   | Each  | Each   | Each  | Mtr  | Each   |
|                          |   |   |  |  |   |  |   |  |  |
|                          |   |   |  |  |   |  | AP.   |  |  |

|                      |   |  |  | E COLTE  |   |  |
|----------------------|---|--|--|--|---|--|
|                      |   | 4  | 28   | 399  | 2,98  |  |
| b) for 75mm dia pipe | Providing and fixing M.S. holder-bat clamps of approved design to sand cast iron (spun) pipe embedded in and including cement concrete blocks 10x10x10cm of 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size) including cost of cutting holes and making good the walls etc:  a) For 100 mm dia pipe | Providing and filling the joints with spun yarn cement slurry and cement mortar 1:2 ( 1 cement: 2 fine sand) in SCI / CI pipes: a) 75mm dia pipe b) 100mm dia pipe | Providing and fixing soil, waste and vent pipes: a) 100mm dia, sand cast iron S&S pipe as per IS: 1729 b) 75mm diameter, sand cast iron S&S pipe as per IS: 1729 | Providing and fixing ball valve (Brass) of approved quality, high or low pressure, with plastic floats complete:  a)15mm nominal bore b) 20mm nominal bore | Providing and fixing brass stop cock of approved quality: a) 20mm nominal bore b) 15mm nominal bore | <ul> <li>c) Concealed pipe, including painting with anti corrosive<br/>bitumastic Paint, cutting chases and making good the wall,<br/>15mm nominal bore</li> </ul> |
| 3% Nos               | 3 ° Nos   | 36 Nos   | 00°124,<br>00°42   | 12 Nos<br>12 Nos   | % No.   | n7.00  |
| ERCH                 | ERCH .  | Each   | 3 8  | 12 Nos<br>10Nos  | Each  | 3  |
|                      |   |  |  |  |   | **   |
|                      |   |  | harring and harry special factors and  |  |   |  |

, S

Providing and fixing decorative high pressure laminated sheet of plain/wood grain in gloss/matt/ suede finish with high density protective surface layer and reverse side of adhesive bonding quality conforms to IS:2046 type including cost of adhesive of approved quality:

a) 1.0 mm thick. 30,00

T S S

Providing and fixing 25mm thick shutters for oup

m) Panelled or panelled & glazed shutters, IInd class teak wood including ISI marked anodised ward etc. aluminium butt hinges with necessary screvs.

> 19.00 いめてい

Note: Coment 6.15 N.7 Co B. SIDT 200 Per N.T Quall of issued from any 0.0.4 Here Deshi") NOW DEDKI.